

## SAFETY DATA SHEET

# 301764 BALSA CEMENT AE0603

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

##### Trade name

301764 BALSA CEMENT AE0603

##### Product no.

301764

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### ▼ Relevant identified uses of the substance or mixture

Adhesive

##### ▼ Uses advised against

Do not discharge into drains or rivers. Contain the spillage using bunding.

#### 1.3. Details of the supplier of the safety data sheet

##### Company and address

##### **Cedesa Ltd**

Chater Lea Building  
Icknield Way, Letchworth  
SG6 1WT Herts  
UK  
+44 (0)1462 480 764

##### Contact person

Quality Department

##### E-mail

quality@cedesa.co.uk

##### Revision

23/09/2024

##### SDS Version

3.0

##### Date of previous version

09/08/2023 (2.0)

#### 1.4. ▼ Emergency telephone number

Healthcare professionals: Dial 0344 892 0111 to reach The National Poisons Information Service (NPIS) (24 hour service)

General public:

England - Dial 111 to reach NHS 111 (24 hour service)

Scotland - Dial 112 to reach NHS 24 (24 hour service)

Wales - Dial 111 or 0845 4647 to reach NHS Direct (24 hour service)

See section 4 "First aid measures".

### SECTION 2: Hazards identification

Classified according to Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

#### 2.1. ▼ Classification of the substance or mixture

Flam. Liq. 2; H225, Highly flammable liquid and vapour.

Acute Tox. 4; H302, Harmful if swallowed.

Skin Irrit. 2; H315, Causes skin irritation.

Eye Dam. 1; H318, Causes serious eye damage.

STOT SE 3; H335, May cause respiratory irritation.

STOT SE 3; H336, May cause drowsiness or dizziness.

#### 2.2. Label elements

##### ▼ Hazard pictogram(s)



#### Signal word

Danger

#### ▼ Hazard statement(s)

Highly flammable liquid and vapour. (H225)  
Harmful if swallowed. (H302)  
Causes skin irritation. (H315)  
Causes serious eye damage. (H318)  
May cause respiratory irritation. (H335)  
May cause drowsiness or dizziness. (H336)

#### Precautionary statement(s)

##### General

If medical advice is needed, have product container or label at hand. (P101)  
Keep out of reach of children. (P102)

##### ▼ Prevention

Wash hands and exposed skin thoroughly after handling. (P264)  
Wear eye protection/protective gloves/protective clothing. (P280)

##### Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.  
Continue rinsing. (P305+P351+P338)  
Immediately call a POISON CENTER/doctor. (P310)

##### ▼ Storage

Store in a well-ventilated place. Keep cool. (P403+P235)

##### Disposal

Dispose of contents/container in accordance with local regulation  
(P501)

#### Hazardous substances

propan-2-ol;isopropyl alcohol;isopropanol  
butan-1-ol;n-butanol  
acetone;propan-2-one;propanone

#### Additional labelling

Not applicable.

#### 2.3. Other hazards

##### ▼ Additional warnings

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.  
This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2023/707.

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable. This product is a mixture.

#### 3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
propan-2-ol;isopropyl alcohol;isopropanol	CAS No.: 67-63-0 EC No.: 200-661-7 UK-REACH: EU 01-2119457558-25-XXXX Index No.: 603-117-00-0	40-60%	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	
butan-1-ol;n-butanol	CAS No.: 71-36-3 EC No.: 200-751-6 UK-REACH: EU 01-2119484630-38-XXXX Index No.: 603-004-00-6	40-60%	Flam. Liq. 3, H226 Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 STOT SE 3, H336	

acetone;propan-2-one;propanone	CAS No.: 67-64-1 EC No.: 200-662-2 UK-REACH: EU 01-2119471330-49-XXXX Index No.: 606-001-00-8	15-25%	EUH066 Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	[1]
--------------------------------	--	--------	---	-----

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

#### Other information

[1] European occupational exposure limit.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

##### Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

##### Skin contact

IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

##### Eye contact

If in eyes: Flush eyes with plenty of water or salt water (20-30 °C) for at least 30 minutes and continue until irritation stops. Remove contact lenses. Make sure you flush under the upper and lower eyelids. Seek medical assistance immediately and continue flushing during transport.

##### ▼ Ingestion

IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

Rinse mouth.

##### ▼ Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

#### 4.2. Most important symptoms and effects, both acute and delayed

The product contains substances that cause serious eye damage. Contact with these substances can cause irreversible effects on the eye / serious eye damage.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

#### 4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

##### Information to medics

Bring this safety data sheet or the label from this product.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

#### 5.2. ▼ Special hazards arising from the substance or mixture

Highly flammable liquid and vapour.

In use may form flammable/explosive vapour-air mixture.

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are

exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO<sub>2</sub>)

### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

Hazchem Code: ●3YE

## SECTION 6: Accidental release measures

### 6.1. ▼ Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Avoid direct contact with spilled substances.

Ensure adequate ventilation, especially in confined areas.

Avoid inhalation of vapours from spilled material.

Contaminated areas may be slippery.

### 6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

Keep unauthorized persons away from the spill

### 6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

### 6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

## SECTION 7: Handling and storage

### 7.1. ▼ Precautions for safe handling

Ground and bond container and receiving equipment.

Use explosion-proof [electrical/lighting/ventilating] equipment.

Use non-sparking tools.

Take action to prevent static discharges.

The product should be tested for peroxides before distillation or evaporation and tested for peroxide formation or discarded after 1 year.

Avoid direct contact with the product.

Peroxide formation may be present anywhere in the container, including the sides, bottom, exterior and threaded cap. Peroxide formation in ppm concentrations may not be visually observable and must be identified through the use of appropriate testing procedures. If any of the following conditions exist, the material may be explosively unstable and will require stabilization prior to use:

1. Material appears to be degraded and or contaminated.

2. Material appears to be discolored.

3. Deterioration or distortion of storage container.

4. Thermal shock (sunlight).

5. Age of material exceeds recommended storage time.

Avoid contact during pregnancy and while nursing.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

### 7.2. ▼ Conditions for safe storage, including any incompatibilities

Store in tightly closed containers and store protected from moisture and light. Containers should be dated when opened and tested periodically for the presence of peroxides. Do not exceed storage time limits.

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Take action to prevent static discharges.

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

**Recommended storage material**

Keep only in original packaging.

**Storage conditions**

Dry, cool and well ventilated

▼ **Incompatible materials**

Strong oxidizing agents  
Strong Alkalis

**7.3. Specific end use(s)**

This product should only be used for applications quoted in section 1.2.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

propan-2-ol;isopropyl alcohol;isopropanol  
 Long term exposure limit (8 hours) (ppm): 400  
 Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 999  
 Short term exposure limit (15 minutes) (ppm): 500  
 Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 1250

butan-1-ol;n-butanol  
 Short term exposure limit (15 minutes) (ppm): 50  
 Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 154  
 Annotations:  
 Sk = Can be absorbed through the skin and lead to systemic toxicity.

acetone;propan-2-one;propanone  
 Long term exposure limit (8 hours) (ppm): 500  
 Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 1210  
 Short term exposure limit (15 minutes) (ppm): 1500  
 Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 3620

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.  
 EH40/2005 Workplace exposure limits (Fourth Edition 2020).

### DNEL

acetone;propan-2-one;propanone

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	62 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	186 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	200 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	1210 mg/m <sup>3</sup>
Short term – Local effects - Workers	Inhalation	2420 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	62 mg/kg bw/day

butan-1-ol;n-butanol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	3.125 mg/kg bw/day
Long term – Local effects - General population	Inhalation	155 mg/m <sup>3</sup>
Long term – Local effects - Workers	Inhalation	310 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Inhalation	55.357 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	1.562 mg/kg bw/day

propan-2-ol;isopropyl alcohol;isopropanol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	319 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	888 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	89 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	500 mg/m <sup>3</sup>

Short term – Systemic effects - General population	Inhalation	178 mg/m <sup>3</sup>
Short term – Systemic effects - Workers	Inhalation	1000 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	26 mg/kg bw/day
Short term – Systemic effects - General population	Oral	51 mg/kg bw/day

## PNEC

acetone;propan-2-one;propanone

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		10.6 mg/L
Freshwater sediment		30.4 mg/kg
Intermittent release (freshwater)		21 mg/L
Marine water		1.06 mg/L
Marine water sediment		3.04 mg/kg
Sewage treatment plant		100 mg/L
Soil		29.5 mg/kg

butan-1-ol;n-butanol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		82 µg/L
Freshwater sediment		324 µg/kg
Intermittent release (freshwater)		2.25 mg/L
Marine water		8.2 µg/L
Marine water sediment		32.4 µg/kg
Sewage treatment plant		2.476 g/L
Soil		16.6 µg/kg

propan-2-ol;isopropyl alcohol;isopropanol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		140.9 mg/L
Freshwater sediment		552 mg/kg
Intermittent release (freshwater)		140.9 mg/L
Marine water		140.9 mg/L
Marine water sediment		552 mg/kg
Predators		160 mg/kg
Sewage treatment plant		2.251 g/L
Soil		28 mg/kg

## 8.2. ▼ Exposure controls

Apply general control to prevent unnecessary exposure

### General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

### Exposure scenarios

There are no exposure scenarios implemented for this product.

### ▼ Exposure limits

Occupational exposure limits have not been defined for the substances in this product.

### ▼ Appropriate technical measures

Ensure that eyewash stations and safety showers are located within easy reach.

Apply standard precautions during use of the product. Avoid inhalation of vapours.

### Hygiene measures

Take off contaminated clothing and wash it before reuse.

### Measures to avoid environmental exposure


No specific requirements.

## Individual protection measures, such as personal protective equipment


### Generally

Use only UKCA marked protective equipment.


### Respiratory Equipment

Type	Class	Colour	Standards	
S/SL	P2	White	EN149	


### Skin protection

Recommended	Type/Category	Standards	
Wear appropriate protection clothing, e.g. coveralls in polypropylene or working clothes in cotton or polyester.	-	-	

### Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Gloves	-	> 360	EN374	

### Eye protection

Type	Standards	
Safety glasses with side shields.	EN166	

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Physical state

Liquid

#### Colour

Clear

#### ▼ Odour / Odour threshold

Characteristic, Solvent

#### ▼ pH

No relevant or available data due to the nature of the product.

#### ▼ Density (g/cm<sup>3</sup>)

No relevant or available data due to the nature of the product.

#### ▼ Kinematic viscosity

200

Test method: No 1 Bobbin @ 20°C

#### ▼ Particle characteristics

Not applicable - product is a liquid

#### Phase changes

#### ▼ Melting point/Freezing point (°C)

No data available

#### Softening point/range (°C)

Does not apply to liquids.

#### ▼ Boiling point (°C)

60

#### ▼ Vapour pressure

No relevant or available data due to the nature of the product.

▼ **Relative vapour density**

Heavier than Air

▼ **Decomposition temperature (°C)**

No data available

**Data on fire and explosion hazards**

▼ **Flash point (°C)**

20

▼ **Flammability (°C)**

The material is ignitable.

▼ **Auto-ignition temperature (°C)**

No data available

▼ **Lower and upper explosion limit (% v/v)**

No relevant or available data due to the nature of the product.

**Solubility**

▼ **Solubility in water**

Miscible

▼ **n-octanol/water coefficient (LogKow)**

No relevant or available data due to the nature of the product.

▼ **Solubility in fat (g/L)**

No relevant or available data due to the nature of the product.

**9.2. Other information**

▼ **Oxidizing properties**

No data available

**Other physical and chemical parameters**

No data available.

## SECTION 10: Stability and reactivity

**10.1. Reactivity**

No data available.

**10.2. Chemical stability**

The product is stable under the conditions, noted in section 7 "Handling and storage".

**10.3. Possibility of hazardous reactions**

None known.

**10.4. ▼ Conditions to avoid**

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

Heat. Hot surfaces. Sources of ignition. Flames.

**10.5. ▼ Incompatible materials**

Strong oxidizing agents

Strong Alkalis

**10.6. Hazardous decomposition products**

The product is not degraded when used as specified in section 1.

## SECTION 11: Toxicological information

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 as retained and amended in UK law**

**Acute toxicity**

Harmful if swallowed.

**Skin corrosion/irritation**

Causes skin irritation.

**Serious eye damage/irritation**

Causes serious eye damage.

**Respiratory sensitisation**

Based on available data, the classification criteria are not met.

**Skin sensitisation**

Based on available data, the classification criteria are not met.

**Germ cell mutagenicity**

Based on available data, the classification criteria are not met.



#### Carcinogenicity

Based on available data, the classification criteria are not met.

#### Reproductive toxicity

Based on available data, the classification criteria are not met.

#### STOT-single exposure

May cause respiratory irritation.

May cause drowsiness or dizziness.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### 11.2. Information on other hazards

##### Long term effects

The product contains substances that cause serious eye damage. Contact with these substances can cause irreversible effects on the eye / serious eye damage.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

##### ▼ Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

##### Other information

propan-2-ol;isopropyl alcohol;isopropanol has been classified by IARC as a group 3 carcinogen.

### SECTION 12: Ecological information

#### 12.1. Toxicity

No data available.

#### 12.2. ▼ Persistence and degradability

Based on available data, the classification criteria are not met.

#### 12.3. ▼ Bioaccumulative potential

Based on available data, the classification criteria are not met.

#### 12.4. Mobility in soil

No data available.

#### 12.5. ▼ Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

#### 12.6. ▼ Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

#### 12.7. Other adverse effects

None known.

### SECTION 13: Disposal considerations

#### ▼ Waste treatment methods

Product is covered by the regulations on hazardous waste.

HP 3 - Flammable

HP 4 - Irritant (skin irritation and eye damage)

HP 5 - Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

HP 6 - Acute toxicity

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

#### EWC code




Not applicable.

#### Specific labelling

#### Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

## SECTION 14: Transport information

	<b>14.1 UN / ID</b>	<b>14.2 UN proper shipping name</b>	<b>14.3 Hazard class(es)</b>	<b>14.4 PG*</b>	<b>14.5 Env**</b>	<b>Other information:</b>
ADR	UN1133	ADHESIVES	Transport hazard class: 3 Label: 3 Classification code: F1 	II	No	Limited quantities: 5 L Tunnel restriction code: (D/E) See below for additional information.
IMDG	UN1133	ADHESIVES	Transport hazard class: 3 Label: 3 Classification code: F1 	II	No	Limited quantities: 5 L EmS: F-E S-D See below for additional information.
IATA	UN1133	ADHESIVES	Transport hazard class: 3 Label: 3 Classification code: F1 	II	No	See below for additional information.

\* Packing group

\*\* Environmental hazards

### Additional information

Although this product is environmentally hazardous, the environmentally hazardous substance mark has been omitted as the product is supplied in packaging with a maximum quantity of 5 L / 5 kg.

-

ADR / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

This product is within scope of the regulations of transport of dangerous goods.

Hazchem Code: ●3YE

### 14.6. Special precautions for user

Not applicable.

### 14.7. Maritime transport in bulk according to IMO instruments

No data available.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### ▼ Restrictions for application

People under the age of 18 shall not be exposed to this product.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

#### Demands for specific education

No specific requirements.

#### ▼ Control of Major Accident Hazards (COMAH) - Categories / dangerous substances

P5c - FLAMMABLE LIQUIDS, Qualifying quantity (lower-tier): 5.000 tonnes / (upper-tier): 50.000 tonnes

#### Regulation on drug precursors

acetone;propan-2-one;propanone is included (Category 3)

#### Regulation on explosives precursors

acetone;propan-2-one;propanone (Annex II)

#### ▼ UK-REACH, Annex XVII

propan-2-ol;isopropyl alcohol;isopropanol is subject to UK-REACH restrictions (entry 40).

butan-1-ol;n-butanol is subject to UK-REACH restrictions (entry 40).

acetone;propan-2-one;propanone is subject to UK-REACH restrictions (entry 40).

#### Additional information

Tactile warning.

#### ▼ Sources

The Management of Health and Safety at Work Regulations 1999.

The Health and Safety at Work etc. Act 1974 Regulations 2013.

Control of Major Accident Hazards (COMAH) Regulations 2015.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

The Controlled Drugs (Drug Precursors) Regulations 2008.

Council Regulation (EC) No 2019/1148 on explosives precursors as retained and amended in UK law.

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

### 15.2. Chemical safety assessment

No

## SECTION 16: Other information

### Full text of H-phrases as mentioned in section 3

H302, Harmful if swallowed.

H315, Causes skin irritation.

H318, Causes serious eye damage.

H319, Causes serious eye irritation.

H335, May cause respiratory irritation.

H336, May cause drowsiness or dizziness.

#### ▼ Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne (European conformity)

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EuPCS = European Product Categorisation System

EWC = European Waste Catalogue  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
GWP = Global warming potential  
IARC = International Agency for Research on Cancer (IARC)  
IATA = International Air Transport Association  
IBC = Intermediate Bulk Container  
IMDG = International Maritime Dangerous Goods  
LogPow = logarithm of the octanol/water partition coefficient  
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
OECD = Organisation for Economic Co-operation and Development  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail  
RRN = REACH Registration Number  
SCL = A specific concentration limit  
SVHC = Substances of Very High Concern  
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure  
STOT-SE = Specific Target Organ Toxicity - Single Exposure  
TWA = Time weighted average  
UN = United Nations  
UVBC = Unknown or variable composition, complex reaction products or of biological materials  
VOC = Volatile Organic Compound  
vPvB = Very Persistent and Very Bioaccumulative

▼ **Additional information**

The classification of the substance/mixture in regard to health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The classification of the mixture in regard to physical hazards has been based on experimental data.

**The safety data sheet is validated by**

Paul Reeds

▼ **Other**

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en