



SAFETY DATA SHEET

AMMO A-Stand part numbers

A.MIG-2500, A.MIG-2501, A.MIG-2502, A.MIG-2451, A.MIG-2452, A.MIG-2453, A.MIG-2454, A.MIG-2455, A.MIG-2456
A.MIG-2457, A.MIG-2458, A.MIG-2459, A.MIG-2460, A.MIG-2461

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier A.MIG-2500, A.MIG-2501, A.MIG-2502, A.MIG-2451, A.MIG-2452, A.MIG-2453, A.MIG-2454, A.MIG-2455, A.MIG-2456, A.MIG-2457, A.MIG-2458, A.MIG-2459, A.MIG-2460, A.MIG-2461

Product name

Product number HR310 (producer reference)

UFI UFI: QMU0-70NJ-T00N-45TY

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Paint.

1.3. Details of the supplier of the safety data sheet

Supplier H&R Hobbies Ltd
Unit 2B, The Follys,
Gaymers Way,
North Walsham,
Norfolk,
NR28 0AN
+44 1692500700
technical@hrhobbies.com

Manufacturer H&R Hobbies Ltd
Unit 2B, The Follys,
Gaymers Way,
North Walsham,
Norfolk,
NR28 0AN
+44 1692500700
technical@hrhobbies.com

1.4. Emergency telephone number

Emergency telephone +44 1692500700 Monday to Friday 8.00am to 5.00pm.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 2 - H225

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H336 STOT RE 2 - H373 Asp. Tox. 1 - H304

Environmental hazards Aquatic Chronic 3 - H412

2.2. Label elements

Hazard pictograms



AMMO A-Stand part numbers

A.MIG-2500, A.MIG-2501, A.MIG-2502, A.MIG-2451, A.MIG-2452, A.MIG-2453, A.MIG-2454, A.MIG-2455,
A.MIG-2456, A.MIG-2457, A.MIG-2458, A.MIG-2459, A.MIG-2460, A.MIG-2461

Signal word	Danger
Hazard statements	H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H373 May cause damage to organs through prolonged or repeated exposure. H304 May be fatal if swallowed and enters airways. H412 Harmful to aquatic life with long lasting effects.
Precautionary statements	P261 Avoid breathing vapour/ spray. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P302+P352 IF ON SKIN: Wash with plenty of water. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P332+P313 If skin irritation occurs: Get medical advice/ attention. P337+P313 If eye irritation persists: Get medical advice/ attention.
Contains	ACETONE, XYLENE, BUTYL ACETATE -norm, Hydrocarbons, C9, aromatics, BUTANOL-norm
Supplementary precautionary statements	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P240 Ground and bond container and receiving equipment. P241 Use explosion-proof electrical equipment. P242 Use non-sparking tools. P243 Take action to prevent static discharges. P260 Do not breathe vapour/ spray. P264 Wash contaminated skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P312 Call a POISON CENTRE/doctor if you feel unwell. P314 Get medical advice/ attention if you feel unwell. P321 Specific treatment (see medical advice on this label). P331 Do NOT induce vomiting. P362+P364 Take off contaminated clothing and wash it before reuse. P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P403+P235 Store in a well-ventilated place. Keep cool. P405 Store locked up. P501 Dispose of contents/ container in accordance with national regulations.

2.3. Other hazards

No additional information available.

SECTION 3: Composition/information on ingredients
3.2. Mixtures

AMMO A-Stand part numbers

A.MIG-2500, A.MIG-2501, A.MIG-2502, A.MIG-2451, A.MIG-2452, A.MIG-2453, A.MIG-2454, A.MIG-2455,
A.MIG-2456, A.MIG-2457, A.MIG-2458, A.MIG-2459, A.MIG-2460, A.MIG-2461

ACETONE		30-60%
CAS number: 67-64-1		EC number: 200-662-2
Classification		
Flam. Liq. 2 - H225		
Eye Irrit. 2 - H319		
STOT SE 3 - H336		
XYLENE		10-30%
CAS number: 1330-20-7		EC number: 215-535-7
Classification		
Flam. Liq. 3 - H226		
Acute Tox. 4 - H312		
Acute Tox. 4 - H332		
Skin Irrit. 2 - H315		
Eye Irrit. 2 - H319		
STOT SE 3 - H335		
STOT RE 2 - H373		
Asp. Tox. 1 - H304		
Aquatic Chronic 3 - H412		
BUTYL ACETATE -norm		5-10%
CAS number: 123-86-4		EC number: 204-658-1
Classification		
Flam. Liq. 3 - H226		
STOT SE 3 - H336		
BUTANOL-norm		1-5%
CAS number: 71-36-3		EC number: 200-751-6
Classification		
Flam. Liq. 3 - H226		
Acute Tox. 4 - H302		
Skin Irrit. 2 - H315		
Eye Dam. 1 - H318		
STOT SE 3 - H335, H336		

AMMO A-Stand part numbers

A.MIG-2500, A.MIG-2501, A.MIG-2502, A.MIG-2451, A.MIG-2452, A.MIG-2453, A.MIG-2454, A.MIG-2455,
A.MIG-2456, A.MIG-2457, A.MIG-2458, A.MIG-2459, A.MIG-2460, A.MIG-2461

TRIETHYLAMINE	<1%
CAS number: 121-44-8	EC number: 204-469-4

Classification

Flam. Liq. 2 - H225
Acute Tox. 4 - H302
Acute Tox. 4 - H312
Acute Tox. 4 - H332
Skin Corr. 1A - H314
Eye Dam. 1 - H318
STOT SE 3 - H335

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures**

General information	First aid personnel should wear appropriate protective equipment during any rescue.
Inhalation	Remove person to fresh air and keep comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Ingestion	Do not induce vomiting. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis. Get medical attention if any discomfort continues.
Skin contact	Wash skin thoroughly with soap and water.
Eye contact	Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyelids widely. If irritation persists: Seek medical attention and bring along these instructions.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Prolonged inhalation of high concentrations may damage respiratory system. During application and drying, solvent vapours will be emitted. Vapours and spray/mists in high concentrations are narcotic.
Ingestion	Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation.
Skin contact	Prolonged contact may cause redness, irritation and dry skin. Discoloration of the skin.
Eye contact	May cause temporary eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

SECTION 5: Firefighting measures**5.1. Extinguishing media**

Suitable extinguishing media	Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Do not use water jet as an extinguisher, as this will spread the fire. Use fire-extinguishing media suitable for the surrounding fire.
-------------------------------------	---

AMMO A-Stand part numbers

A.MIG-2500, A.MIG-2501, A.MIG-2502, A.MIG-2451, A.MIG-2452, A.MIG-2453, A.MIG-2454, A.MIG-2455,
A.MIG-2456, A.MIG-2457, A.MIG-2458, A.MIG-2459, A.MIG-2460, A.MIG-2461

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Flammable liquid and vapour. Solvent vapours may form explosive mixtures with air. Containers can burst violently or explode when heated, due to excessive pressure build-up.

Hazardous combustion products Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of carbon. Oxides of nitrogen.

5.3. Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material. Provide adequate ventilation.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Wear protective equipment as described in Section 8 of this data sheet. Clear up spills immediately and dispose of waste safely. Small Spillages: Collect spillage. Large Spillages: Absorb spillage with inert, damp, non-combustible material. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. For waste disposal, see Section 13.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Usage precautions Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimise spills. Keep container tightly sealed when not in use. Avoid the formation of mists. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment.

AMMO A-Stand part numbers

A.MIG-2500, A.MIG-2501, A.MIG-2502, A.MIG-2451, A.MIG-2452, A.MIG-2453, A.MIG-2454, A.MIG-2455,
A.MIG-2456, A.MIG-2457, A.MIG-2458, A.MIG-2459, A.MIG-2460, A.MIG-2461

Advice on general occupational hygiene

Wash promptly if skin becomes contaminated. Take off contaminated clothing. Take off contaminated clothing and wash it before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

7.2. Conditions for safe storage, including any incompatibilities**Storage precautions**

Store away from incompatible materials (see Section 10). Keep only in the original container. Keep container tightly closed and in a well-ventilated place. Keep containers upright.

Storage class

Flammable liquid storage. The storage and use of this product is subject to the Dangerous Substances and Explosive Atmospheres Regulations (DSEAR). The requirements are given in the HSE Approved Code of Practice and Guidance, Storage of Dangerous Substances: DSEAR. Up to 50 litres of liquids with a flash point below 32C may be kept in a workroom provided they are kept in closed containers in a marked, fire-resisting cupboard or bin. Larger quantities must be kept in a separate, marked storeroom conforming to the structural requirements contained in the HSE guidance note Storage of Flammable Liquids in Containers.

7.3. Specific end use(s)**Specific end use(s)**

The identified uses for this product are detailed in Section 1.2.

Usage description

Ensure that waste and contaminated materials are collected and removed from the work area as soon as possible in a suitably labelled container.

SECTION 8: Exposure controls/Personal protection**8.1. Control parameters****Occupational exposure limits****ACETONE**

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m³

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m³

XYLENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m³

Sk

BUTYL ACETATE -norm

Long-term exposure limit (8-hour TWA): WEL 150 ppm 724 mg/m³

Short-term exposure limit (15-minute): WEL 200 ppm 966 mg/m³

BUTANOL-norm

Long-term exposure limit (8-hour TWA): WEL

Short-term exposure limit (15-minute): WEL 50 ppm(Sk) 154 mg/m³(Sk)

TRIETHYLAMINE

Long-term exposure limit (8-hour TWA): WEL 2 ppm(Sk) 8 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 4 ppm(Sk) 17 mg/m³(Sk)

WEL = Workplace Exposure Limit.

Sk = Can be absorbed through the skin.

ACETONE (CAS: 67-64-1)

AMMO A-Stand part numbers

A.MIG-2500, A.MIG-2501, A.MIG-2502, A.MIG-2451, A.MIG-2452, A.MIG-2453, A.MIG-2454, A.MIG-2455,
A.MIG-2456, A.MIG-2457, A.MIG-2458, A.MIG-2459, A.MIG-2460, A.MIG-2461

DNEL

Workers - Dermal; Long term systemic effects: 186 mg/kg/day
 Workers - Inhalation; Short term local effects: 2420 mg/m³
 Workers - Inhalation; Long term systemic effects: 1210 mg/m³
 Industry - Dermal; Long term : 186 mg/kg/day
 Industry - Inhalation; Short term : 2420 mg/m³
 Industry - Inhalation; Long term : 1210 mg/m³
 Consumer - Oral; Long term : 62 mg/kg/day
 Consumer - Dermal; Long term : 62 mg/kg/day
 Consumer - Inhalation; Long term : 200 mg/m³

PNEC

- Sediment (Freshwater); 30.4 mg/kg
 - Sediment (Marinewater); 3.04 mg/kg
 - marine water; 1.06 mg/l
 - Soil; 29.5 mg/kg

XYLENE (CAS: 1330-20-7)

DNEL

Consumer - Dermal; Long term systemic effects: 108 mg/kg/day
 Workers - Dermal; Long term systemic effects: 180 mg/kg/day
 Consumer - Inhalation; Short term local effects: 174 mg/m³
 Consumer - Inhalation; Short term systemic effects: 174 mg/m³
 Workers - Inhalation; Short term systemic effects: 289 mg/m³
 Workers - Inhalation; Short term local effects: 289 mg/m³
 Consumer - Inhalation; Long term systemic effects: 14.8 mg/m³
 Workers - Inhalation; Long term systemic effects: 77 mg/m³

Hydrocarbons, C9, aromatics (CAS: 128601-23-0)

DNEL

Consumer - Oral; Long term systemic effects: 11 mg/kg/day
 Consumer - Dermal; Long term systemic effects: 11 mg/kg/day
 Consumer - Inhalation; Long term systemic effects: 32 mg/m³
 Industry/Professional - Dermal; Long term systemic effects: 25 mg/kg/day
 Industry/Professional - Inhalation; Long term systemic effects: 100 mg/m³

8.2. Exposure controls**Appropriate engineering controls**

Provide adequate ventilation. Good general ventilation should be adequate to control worker exposure to airborne contaminants. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimise worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure operatives are trained to minimise exposure.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with European Standard EN166. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn:

Hand protection

To protect hands from chemicals, gloves should comply with European Standard EN374. Wear protective gloves made of the following material: Nitrile rubber.

Other skin and body protection

Wear apron or protective clothing in case of contact.

AMMO A-Stand part numbers

A.MIG-2500, A.MIG-2501, A.MIG-2502, A.MIG-2451, A.MIG-2452, A.MIG-2453, A.MIG-2454, A.MIG-2455, A.MIG-2456, A.MIG-2457, A.MIG-2458, A.MIG-2459, A.MIG-2460, A.MIG-2461

Respiratory protection	Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with European Standard EN14387. Full face mask respirators with replaceable filter cartridges should comply with European Standard EN136. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. Wear a respirator fitted with the following cartridge: Gas filter, type A2.
Environmental exposure controls	Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

SECTION 9: Physical and chemical properties
--

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Various colours.
Odour	Acetone.
Odour threshold	No information available.
pH	Not relevant.
Melting point	No information available.
Initial boiling point and range	No information available.
Flash point	-14°C Closed cup.
Evaporation rate	No information available.
Evaporation factor	No information available.
Flammability (solid, gas)	No information available.
Upper/lower flammability or explosive limits	No information available.
Other flammability	No information available.
Vapour pressure	No information available.
Vapour density	No information available.
Relative density	No information available.
Bulk density	No information available.
Solubility(ies)	Immiscible with water.
Partition coefficient	Not determined.
Auto-ignition temperature	No information available.
Decomposition Temperature	No information available.
Viscosity	No information available.
Explosive properties	No information available.
Explosive under the influence of a flame	No

AMMO A-Stand part numbers

A.MIG-2500, A.MIG-2501, A.MIG-2502, A.MIG-2451, A.MIG-2452, A.MIG-2453, A.MIG-2454, A.MIG-2455,
A.MIG-2456, A.MIG-2457, A.MIG-2458, A.MIG-2459, A.MIG-2460, A.MIG-2461

Oxidising properties Not determined.
Comments Information given is applicable to the product as supplied.

9.2. Other information

Other information None.

SECTION 10: Stability and reactivity**10.1. Reactivity**

Reactivity See the other subsections of this section for further details.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions The following materials may react strongly with the product: Oxidising agents.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Containers can burst violently or explode when heated, due to excessive pressure build-up. Static electricity and formation of sparks must be prevented.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents. Acids - organic.

10.6. Hazardous decomposition products

Hazardous decomposition products Does not decompose when used and stored as recommended. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: Toxicological information**11.1. Information on toxicological effects**

Toxicological effects There is no data available on the mixture itself. The mixture has been assessed following the EC 1272/2008 regulation and classified for toxicological hazards accordingly. See sections 2 and 3 for details.

Acute toxicity - oral

ATE oral (mg/kg) 22,727.27

Acute toxicity - dermal

ATE dermal (mg/kg) 8,730.16

Acute toxicity - inhalation

ATE inhalation (gases ppm) 35,714.29

ATE inhalation (vapours mg/l) 87.3

ATE inhalation (dusts/mists mg/l) 11.9

Skin corrosion/irritation

Skin corrosion/irritation No information available.

Serious eye damage/irritation

Serious eye damage/irritation No information available.

AMMO A-Stand part numbers

A.MIG-2500, A.MIG-2501, A.MIG-2502, A.MIG-2451, A.MIG-2452, A.MIG-2453, A.MIG-2454, A.MIG-2455,
A.MIG-2456, A.MIG-2457, A.MIG-2458, A.MIG-2459, A.MIG-2460, A.MIG-2461

Respiratory sensitisation

Respiratory sensitisation No information available.

Skin sensitisation

Skin sensitisation No information available.

Germ cell mutagenicity

Genotoxicity - in vitro No information available.

Genotoxicity - in vivo No information available.

Carcinogenicity

IARC carcinogenicity None of the ingredients are listed or exempt.

Reproductive toxicity

Reproductive toxicity - fertility No information available.

Reproductive toxicity - development Not available.

Specific target organ toxicity - single exposure

STOT - single exposure No information available.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure No information available.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

Inhalation

Prolonged inhalation of high concentrations may damage respiratory system. In high concentrations, vapours are narcotic and may cause headache, fatigue, dizziness and nausea.

Ingestion

Symptoms following overexposure may include the following: Nausea, vomiting. Diarrhoea.

Skin contact

The product contains organic solvents. May be absorbed through the skin. Acts as a defatting agent on skin. May cause cracking of skin, and eczema.

Eye contact

May cause temporary eye irritation.

Acute and chronic health hazards

Swallowing concentrated chemical may cause severe internal injury.

Medical symptoms

Upper respiratory irritation. Nausea, vomiting. Allergic rash.

Medical considerations

Skin disorders and allergies. Avoid vomiting and normal rinse of stomach because of risk of aspiration.

Toxicological information on ingredients.**ACETONE****Acute toxicity - oral**

Acute toxicity oral (LD₅₀ mg/kg) 5,800.0

Species Rat

ATE oral (mg/kg) 5,800.0

Acute toxicity - dermal

AMMO A-Stand part numbers

A.MIG-2500, A.MIG-2501, A.MIG-2502, A.MIG-2451, A.MIG-2452, A.MIG-2453, A.MIG-2454, A.MIG-2455,
A.MIG-2456, A.MIG-2457, A.MIG-2458, A.MIG-2459, A.MIG-2460, A.MIG-2461

**Acute toxicity dermal (LD₅₀ 7,800.0
mg/kg)**

Species Rabbit

ATE dermal (mg/kg) 7,800.0

Acute toxicity - inhalation

**Acute toxicity inhalation
(LC₅₀ dust/mist mg/l)** 76.0

Species Rat

XYLENEAcute toxicity - oral

**Acute toxicity oral (LD₅₀ 4,300.0
mg/kg)**

Species Rat

Acute toxicity - dermal

**Acute toxicity dermal (LD₅₀ 3,200.0
mg/kg)**

Species Rabbit

ATE dermal (mg/kg) 1,100.0

Carcinogenicity

IARC carcinogenicity IARC Group 3 Not classifiable as to its carcinogenicity to humans.

Hydrocarbons, C9, aromaticsAcute toxicity - oral

**Acute toxicity oral (LD₅₀ 3,592.0
mg/kg)**

Species Rat

Acute toxicity - dermal

**Acute toxicity dermal (LD₅₀ 3,161.0
mg/kg)**

Species Rabbit

Acute toxicity - inhalation

**Acute toxicity inhalation
(LC₅₀ vapours mg/l)** 6,194.0

Species Rat

Serious eye damage/irritation

**Serious eye
damage/irritation** Slightly irritating.

Respiratory sensitisation

Respiratory sensitisation Not sensitising.

AMMO A-Stand part numbers

A.MIG-2500, A.MIG-2501, A.MIG-2502, A.MIG-2451, A.MIG-2452, A.MIG-2453, A.MIG-2454, A.MIG-2455,
A.MIG-2456, A.MIG-2457, A.MIG-2458, A.MIG-2459, A.MIG-2460, A.MIG-2461

Carcinogenicity

Carcinogenicity No evidence

Specific target organ toxicity - single exposure

Target organs Central nervous system Respiratory system, lungs

Aspiration hazard

Aspiration hazard Kinematic viscosity > 20.5 mm²/s. The product viscosity is greater than the upper limit assigned for classification. Although not classified, the product contains mineral oil. If aspirated into the lungs e.g. through vomiting after ingestion, admit to hospital immediately.

BUTANOL-norm**Acute toxicity - oral**

Acute toxicity oral (LD₅₀ mg/kg) 2,292.0

Species Rat

ATE oral (mg/kg) 500.0

SECTION 12: Ecological information

Ecotoxicity There are no data on the ecotoxicity of this product. The mixture has been assessed following the EC 1272/2008 regulation and classified for toxicological hazards accordingly.

12.1. Toxicity**Ecological information on ingredients.****ACETONE****Acute aquatic toxicity**

Acute toxicity - fish EC₅₀, 96 hours: 8300 mg/l, *Lepomis macrochirus* (Bluegill)
LC₅₀, 96 hours: 5540 mg/l, *Oncorhynchus mykiss* (Rainbow trout)
LC₅₀, 96 hours: >100 mg/l, *Pimephales promelas* (Fat-head Minnow)

Acute toxicity - aquatic invertebrates EC₅₀, : 8800 mg/l, *Daphnia magna*
NOEC, 28 days: 2.212 mg/l, *Daphnia magna*

Acute toxicity - microorganisms , : 1000 mg/l, Activated sludge

XYLENE**Acute aquatic toxicity**

Acute toxicity - fish LOEC, : >1-<10 mg/l, Fish

Acute toxicity - aquatic invertebrates LOEC, : >1-<10 mg/l,

Hydrocarbons, C9, aromatics**Acute aquatic toxicity**

Acute toxicity - fish LC₅₀, 96 hours: 9.2 mg/l, Fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 3.2 mg/l, *Daphnia magna*

AMMO A-Stand part numbers

A.MIG-2500, A.MIG-2501, A.MIG-2502, A.MIG-2451, A.MIG-2452, A.MIG-2453, A.MIG-2454, A.MIG-2455,
A.MIG-2456, A.MIG-2457, A.MIG-2458, A.MIG-2459, A.MIG-2460, A.MIG-2461

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

Ecological information on ingredients.**ACETONE**

Biodegradation Water - Degradation 91: 28 days

Chemical oxygen demand 2.21 g O₂/g substance

Hydrocarbons, C9, aromatics

Biodegradation The substance is readily biodegradable.
Degradation (%)

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not determined.

Ecological information on ingredients.**ACETONE**

Partition coefficient : -0.24

Hydrocarbons, C9, aromatics

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

Ecological information on ingredients.**ACETONE**

Adsorption/desorption coefficient Water - : 1.5 @ 20°C

Henry's law constant 3311 Pa m³/mol @ 25°C

Hydrocarbons, C9, aromatics

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

Ecological information on ingredients.**Hydrocarbons, C9, aromatics**

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

AMMO A-Stand part numbers

A.MIG-2500, A.MIG-2501, A.MIG-2502, A.MIG-2451, A.MIG-2452, A.MIG-2453, A.MIG-2454, A.MIG-2455,
A.MIG-2456, A.MIG-2457, A.MIG-2458, A.MIG-2459, A.MIG-2460, A.MIG-2461

12.6. Other adverse effects

Other adverse effects None known.

Ecological information on ingredients.**Hydrocarbons, C9, aromatics**

Other adverse effects Not determined.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

General information	The generation of waste should be minimised or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out.
Disposal methods	Do not empty into drains. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents. Waste packaging should be collected for reuse or recycling.
Waste class	When this coating, in its liquid state, as supplied, becomes a waste, it is categorised as hazardous waste, with code 08 01 11* (SOLVENT BASED WASTE). Part used containers, not drained and/or rigorously scraped out and containing dried residues of the supplied coating, are categorised as hazardous waste, with code 08 01 11* (SOLVENT BASED LIQUID WASTE). If mixed with other wastes, the above waste code may not be applicable. Used containers, drained and/or rigorously scraped out and containing dry residues of the supplied coating, are categorised as non-hazardous waste, with code 15 01 02 (plastic packaging) or 15 01 04 (metal packaging).

SECTION 14: Transport information

General For limited quantity packaging/limited load information, consult the relevant modal documentation using the data shown in this section.

14.1. UN number

UN No. (ADR/RID)	1263
UN No. (IMDG)	1263
UN No. (ICAO)	1263
UN No. (ADN)	1263

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	PAINT
Proper shipping name (IMDG)	PAINT
Proper shipping name (ICAO)	PAINT
Proper shipping name (ADN)	PAINT

14.3. Transport hazard class(es)

ADR/RID class	3
----------------------	---

AMMO A-Stand part numbers

A.MIG-2500, A.MIG-2501, A.MIG-2502, A.MIG-2451, A.MIG-2452, A.MIG-2453, A.MIG-2454, A.MIG-2455,
A.MIG-2456, A.MIG-2457, A.MIG-2458, A.MIG-2459, A.MIG-2460, A.MIG-2461

IMDG class 3

ICAO class/division 3

ADN class 3

14.4. Packing group

ADR/RID packing group II

IMDG packing group II

ICAO packing group II

ADN packing group II

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Always transport in closed containers that are upright and secure.

LQ Volume(max)

LQ Restrictions

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

**Annex II of MARPOL 73/78
and the IBC Code**

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Commission Regulation (EU) No 2020/878 of 18th June 2020.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

AMMO A-Stand part numbers

A.MIG-2500, A.MIG-2501, A.MIG-2502, A.MIG-2451, A.MIG-2452, A.MIG-2453, A.MIG-2454, A.MIG-2455,
A.MIG-2456, A.MIG-2457, A.MIG-2458, A.MIG-2459, A.MIG-2460, A.MIG-2461

Abbreviations and acronyms used in the safety data sheet

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail.
IATA: International Air Transport Association.
ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air.
IMDG: International Maritime Dangerous Goods.
CAS: Chemical Abstracts Service.
ATE: Acute Toxicity Estimate.
LC₅₀: Lethal Concentration to 50 % of a test population.
LD₅₀: Lethal Dose to 50% of a test population (Median Lethal Dose).
EC₅₀: 50% of maximal Effective Concentration.
PBT: Persistent, Bioaccumulative and Toxic substance.
vPvB: Very Persistent and Very Bioaccumulative.

Classification abbreviations and acronyms

Acute Tox. = Acute toxicity
Aquatic Acute = Hazardous to the aquatic environment (acute)
Aquatic Chronic = Hazardous to the aquatic environment (chronic)
Asp. Tox. = Aspiration hazard
Flam. Liq. = Flammable liquid
STOT RE = Specific target organ toxicity-repeated exposure
STOT SE = Specific target organ toxicity-single exposure

Training advice Read and follow manufacturer's recommendations.

Revision comments NOTE: Lines within the margin indicate significant changes from the previous revision.

Issued by HS&E Manager.

Revision date 20/05/2022

Revision 3

Supersedes date 18/05/2022

SDS number 21087

Hazard statements in full

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.