

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024

Version number 2.0 (replaces version 1.0)

Revision: 07.06.2024

1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** Mr. SUPER CLEAR UV (Aerosol)
- **Article number:** B-522
- **Relevant identified uses of the substance or mixture and uses advised against**
 No further relevant information available.
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 GSI EUROPE - Import + Export GmbH
 Louise-Dumont-Str. 31
 40211 DÜSSELDORF
 GERMANY
- **Further information obtainable from:** Hobby Department
- **Emergency telephone number:** During normal opening times: +49/211/1665 98420

2 Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



health hazard

Carc. 2 H351 Suspected of causing cancer.



corrosion

Eye Dam. 1 H318 Causes serious eye damage.



Skin Irrit. 2 H315 Causes skin irritation.

- **Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
 The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

GB

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024

Version number 2.0 (replaces version 1.0)

Revision: 07.06.2024

Trade name: Mr. SUPER CLEAR UV (Aerosol)

(Contd. of page 1)

· **Hazard pictograms**



GHS02 GHS05 GHS08

· **Signal word** Danger

· **Hazard-determining components of labelling:**

butan-1-ol

4-methylpentan-2-one

· **Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H351 Suspected of causing cancer.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 115-10-6	dimethyl ether	>25–≤50%
EINECS: 204-065-8	⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	
CAS: 71-36-3	butan-1-ol	10%
EINECS: 200-751-6	⚠ Flam. Liq. 3, H226; ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	

(Contd. on page 3)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024

Version number 2.0 (replaces version 1.0)

Revision: 07.06.2024

Trade name: Mr. SUPER CLEAR UV (Aerosol)

(Contd. of page 2)

CAS: 108-10-1 EINECS: 203-550-1	4-methylpentan-2-one ⚠ Flam. Liq. 2, H225; ⚠ Carc. 2, H351; ⚠ Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066 ATE: LC50/4 h inhalative: 11 mg/l	10%
CAS: 123-42-2 EINECS: 204-626-7	4-hydroxy-4-methylpentan-2-one ⚠ Flam. Liq. 3, H226; ⚠ Eye Irrit. 2, H319 Specific concentration limit: Eye Irrit. 2; H319: C ≥ 10 %	10%
CAS: 64-17-5 EINECS: 200-578-6	ethanol ⚠ Flam. Liq. 2, H225	>2.5–≤10%
CAS: 78-93-3 EINECS: 201-159-0	butanone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	>2.5–<10%
CAS: 123-86-4 EINECS: 204-658-1	n-butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336, EUH066	>2.5–≤10%
CAS: 141-78-6 EINECS: 205-500-4	ethyl acetate ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	>2.5–<10%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

GB

(Contd. on page 4)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024

Version number 2.0 (replaces version 1.0)

Revision: 07.06.2024

Trade name: Mr. SUPER CLEAR UV (Aerosol)

(Contd. of page 3)

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Use neutralising agent.
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Precautions for safe handling** Open and handle receptacle with care.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

115-10-6 dimethyl ether

WEL	Short-term value: 958 mg/m ³ , 500 ppm
	Long-term value: 766 mg/m ³ , 400 ppm

71-36-3 butan-1-ol

WEL	Short-term value: 154 mg/m ³ , 50 ppm
Sk	

108-10-1 4-methylpentan-2-one

WEL	Short-term value: 416 mg/m ³ , 100 ppm
	Long-term value: 208 mg/m ³ , 50 ppm
Sk, BMGV	

(Contd. on page 5)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024

Version number 2.0 (replaces version 1.0)

Revision: 07.06.2024

Trade name: Mr. SUPER CLEAR UV (Aerosol)

(Contd. of page 4)

123-42-2 4-hydroxy-4-methylpentan-2-one

WEL Short-term value: 362 mg/m³, 75 ppm
 Long-term value: 241 mg/m³, 50 ppm

64-17-5 ethanol

WEL Long-term value: 1920 mg/m³, 1000 ppm

78-93-3 butanone

WEL Short-term value: 899 mg/m³, 300 ppm
 Long-term value: 600 mg/m³, 200 ppm
 Sk, BMGV

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm
 Long-term value: 724 mg/m³, 150 ppm

141-78-6 ethyl acetate

WEL Short-term value: 1468 mg/m³, 400 ppm
 Long-term value: 734 mg/m³, 200 ppm

· **Ingredients with biological limit values:**

108-10-1 4-methylpentan-2-one

BMGV 20 µmol/L
 Medium: urine
 Sampling time: post shift
 Parameter: 4-methylpentan-2-one

78-93-3 butanone

BMGV 70 µmol/L
 Medium: urine
 Sampling time: post shift
 Parameter: butan-2-one

· **Additional information:** The lists valid during the making were used as basis.

· **Exposure controls**

· **Appropriate engineering controls** No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing
 Wash hands before breaks and at the end of work.
 Store protective clothing separately.
 Avoid contact with the skin.
 Avoid contact with the eyes and skin.

· **Respiratory protection:** Not required.

(Contd. on page 6)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024

Version number 2.0 (replaces version 1.0)

Revision: 07.06.2024

Trade name: Mr. SUPER CLEAR UV (Aerosol)

(Contd. of page 5)

· Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Physical state

Aerosol

· Colour:

Colourless

· Odour:

Solvent-like

· Odour threshold:

Not determined.

· Melting point/freezing point:

Undetermined.

· Boiling point or initial boiling point and boiling range

Not applicable, as aerosol.

· Flammability

Not applicable.

· Lower and upper explosion limit

· Lower:

50 g/m³ (108-10-1 4-methylpentan-2-one)

· Upper:

390 g/m³ (123-42-2 4-hydroxy-4-methylpentan-2-one)

· Flash point:

Not applicable, as aerosol.

· Decomposition temperature:

Not determined.

(Contd. on page 7)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024

Version number 2.0 (replaces version 1.0)

Revision: 07.06.2024

Trade name: Mr. SUPER CLEAR UV (Aerosol)

(Contd. of page 6)

· pH	Mixture is non-polar/aprotic.
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic:	Not determined.
· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure:	Not determined.
· Density and/or relative density	
· Density at 20 °C:	0.85 g/cm ³
· Relative density	Not determined.
· Bulk density:	850 kg/m ³
· Vapour density	Not determined.
· Other information	
· Appearance:	
· Form:	Aerosol
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Not determined.
· Solvent content:	
· Organic solvents:	90.0 %
· VOC (EC)	90.00 %
· Solids content:	0.0 %
· Change in condition	
· Evaporation rate	Not applicable.
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Extremely flammable aerosol. Pressurised container: May burst if heated.
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void

(Contd. on page 8)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024

Version number 2.0 (replaces version 1.0)

Revision: 07.06.2024

Trade name: Mr. SUPER CLEAR UV (Aerosol)

(Contd. of page 7)

- | | |
|----------------------------------|------|
| · Oxidising solids | Void |
| · Organic peroxides | Void |
| · Corrosive to metals | Void |
| · Desensitised explosives | Void |

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values relevant for classification:**

ATE (Acute Toxicity Estimates)

Oral	LD50	7,900 mg/kg (rat)
Inhalative	LC50/4 h	83–166 mg/l (ATE)

115-10-6 dimethyl ether

Inhalative	LC50/4 h	308 mg/l (rat)
------------	----------	----------------

71-36-3 butan-1-ol

Oral	LD50	790 mg/kg (rat)
Dermal	LD50	3,400 mg/kg (rabbit)
Inhalative	LC50/4 h	8,000 mg/l (rat)

108-10-1 4-methylpentan-2-one

Oral	LD50	2,080 mg/kg (rat)
Dermal	LD50	16,000 mg/kg (rab)
Inhalative	LC50/4 h	11 mg/l (ATE) 8.3–16.6 mg/l (rat)

123-42-2 4-hydroxy-4-methylpentan-2-one

Oral	LD50	4,000 mg/kg (rat)
------	------	-------------------

(Contd. on page 9)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024

Version number 2.0 (replaces version 1.0)

Revision: 07.06.2024

Trade name: Mr. SUPER CLEAR UV (Aerosol)

(Contd. of page 8)

Dermal	LD50	13,630 mg/kg (rab)
64-17-5 ethanol		
Oral	LD50	7,060 mg/kg (rat)
Inhalative	LC50/4 h	20,000 mg/l (rat)
78-93-3 butanone		
Oral	LD50	3,300 mg/kg (rat)
Dermal	LD50	5,000 mg/kg (rabbit)
123-86-4 n-butyl acetate		
Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>21 mg/l (rat)
141-78-6 ethyl acetate		
Oral	LD50	5,620 mg/kg (rabbit)
Inhalative	LC50/4 h	1,600 mg/l (rat)

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye damage.
- **Carcinogenicity** Suspected of causing cancer.
- **Information on other hazards**

· **Endocrine disrupting properties**

78-93-3	butanone	List II
---------	----------	---------

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **Other adverse effects**
- **Additional ecological information:**
- **General notes:**
 Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
 Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

(Contd. on page 10)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024

Version number 2.0 (replaces version 1.0)

Revision: 07.06.2024

Trade name: Mr. SUPER CLEAR UV (Aerosol)



Must not reach sewage water or drainage ditch undiluted or unneutralised.

(Contd. of page 9)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---|---------------------|
| · UN number or ID number | UN1950 |
| · ADR, IMDG, IATA | |
| · UN proper shipping name | 1950 AEROSOLS |
| · ADR | AEROSOLS |
| · IMDG | Aerosols, flammable |
| · IATA | |
| · Transport hazard class(es) | |
| · ADR | |
|  | |
| · Class | 2 5F Gases. |
| · Label | 2.1 |
| · IMDG, IATA | |
|  | |
| · Class | 2.1 Gases. |
| · Label | 2.1 |
| · Packing group | not regulated |
| · ADR, IMDG, IATA | |
| · Environmental hazards: | Not applicable. |
| · Special precautions for user | Warning: Gases. |

(Contd. on page 11)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024

Version number 2.0 (replaces version 1.0)

Revision: 07.06.2024

Trade name: Mr. SUPER CLEAR UV (Aerosol)

(Contd. of page 10)

· Hazard identification number (Kemler code): -	
· EMS Number:	F-D,S-U
· Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Poisons Act**

· **Regulated explosives precursors**

None of the ingredients is listed.

(Contd. on page 12)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024

Version number 2.0 (replaces version 1.0)

Revision: 07.06.2024

Trade name: Mr. SUPER CLEAR UV (Aerosol)

(Contd. of page 11)

· **Regulated poisons**

None of the ingredients is listed.

· **Reportable explosives precursors**

None of the ingredients is listed.

· **Reportable poisons**

None of the ingredients is listed.

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category** P3a FLAMMABLE AEROSOLS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- EUH066 Repeated exposure may cause skin dryness or cracking.

· **Department issuing SDS:** Hobby Department

· **Contact:** -

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

(Contd. on page 13)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024

Version number 2.0 (replaces version 1.0)

Revision: 07.06.2024

Trade name: Mr. SUPER CLEAR UV (Aerosol)

(Contd. of page 12)

LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
ATE: Acute toxicity estimate values
Flam. Gas 1A: Flammable gases – Category 1A
Aerosol 1: Aerosols – Category 1
Press. Gas (Comp.): Gases under pressure – Compressed gas
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Carc. 2: Carcinogenicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
· *** Data compared to the previous version altered.**

GB