Page 1/12

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024 Version number 2.0 (replaces version 1.0) Revision: 07.06.2024

### 1 Identification of the substance/mixture and of the company/undertaking

· Product identifier

· Trade name: Mr. TOPCOAT GLOSS (Aerosol)

· Article number: B-501

Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture Coating

· Details of the supplier of the safety data sheet

Manufacturer/Supplier:

GSI EUROPE - Import + Export GmbH

Louise-Dumont-Str. 31 40211 DÜSSELDORF

**GERMANY** 

· Further information obtainable from: Hobby Department

· Emergency telephone number: During normal opening times: +49/211/1665 98420

#### 2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Eye Dam. 1 H318 Causes serious eye damage.



Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)



Page 2/12

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024 Version number 2.0 (replaces version 1.0) Revision: 07.06.2024

Trade name: Mr. TOPCOAT GLOSS (Aerosol)

· Hazard pictograms

(Contd. of page 1)







GHS02 GHS05 GHS07

- Signal word Danger
- · Hazard-determining components of labelling:

butanol

propan-2-ol

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H318 Causes serious eye damage.H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

### 3 Composition/information on ingredients

- · Mixtures
- **Description:** Mixture of substances listed below with nonhazardous additions.

٠	Dan	gerous	com	ponent	ts:
---	-----	--------	-----	--------	-----

 >50–≤100%

(Contd. on page 3)

Page 3/12

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024 Version number 2.0 (replaces version 1.0) Revision: 07.06.2024

Trade name: Mr. TOPCOAT GLOSS (Aerosol)

	propan-2-ol  Flam. Liq. 2, H225;	Contd. of page 2) ≥20–≤25%
CAS: 64-17-5	ethanol  Flam. Liq. 2, H225	>2.5–≤10%
0.10.100.	butanol Flam. Liq. 3, H226;  Eye Dam. 1, H318;  Skin Irrit. 2, H315; STOT SE 3, H335-H336	≥3–<10%
EINECS: 203-905-0	2-butoxyethanol Acute Tox. 3, H311; Acute Tox. 3, H331; Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319 ATE: LD50 oral: 1,200 mg/kg LC50/4 h inhalative: 3 mg/l	>2.5-<10%

<sup>·</sup> Additional information: For the wording of the listed hazard phrases refer to section 16.

#### 4 First aid measures

- Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### **5 Firefighting measures**

- · Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

#### **6 Accidental release measures**

- · Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)

Page 4/12

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024 Version number 2.0 (replaces version 1.0) Revision: 07.06.2024

Trade name: Mr. TOPCOAT GLOSS (Aerosol)

(Contd. of page 3)

· Methods and material for containment and cleaning up:

Use neutralising agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### 7 Handling and storage

- · Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection: Keep ignition sources away Do not smoke.
- · Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

	rol parameters dients with limit values that require monitoring at the workplace:
	0-6 dimethyl ether
WEL	Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm
67-63	-0 propan-2-ol
WEL	Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm
64-17	-5 ethanol
WEL	Long-term value: 1920 mg/m³, 1000 ppm
78-83	-1 butanol
WEL	Short-term value: 231 mg/m³, 75 ppm Long-term value: 154 mg/m³, 50 ppm
111-7	6-2 2-butoxyethanol
WEL	Short-term value: 246 mg/m³, 50 ppm Long-term value: 123 mg/m³, 25 ppm Sk, BMGV

(Contd. on page 5)

Page 5/12

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024 Version number 2.0 (replaces version 1.0) Revision: 07.06.2024

Trade name: Mr. TOPCOAT GLOSS (Aerosol)

(Contd. of page 4)

#### · Ingredients with biological limit values:

### 111-76-2 2-butoxyethanol

BMGV 240 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: butoxyacetic acid

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

#### · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Hand protection



#### Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)



Page 6/12

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024 Version number 2.0 (replaces version 1.0) Revision: 07.06.2024

Trade name: Mr. TOPCOAT GLOSS (Aerosol)

· Eye/face protection

(Contd. of page 5)



Tightly sealed goggles

### 9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Odour:
Odour threshold:
Melting point/freezing point:

Aerosol
Colourless
Solvent-like
Not determined.
Undetermined.

· Boiling point or initial boiling point and boiling

range Not applicable, as aerosol.

· Flammability Not applicable.

Lower and upper explosion limit

Lower: Not determined.Upper: Not determined.

· Flash point: Not applicable, as aerosol.

• Decomposition temperature: Not determined.

• **pH** Mixture is non-polar/aprotic.

· Viscosity:

Kinematic viscosityDynamic:Not determined.Not determined.

· Solubility

water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined. · Vapour pressure: Not determined.

· Density and/or relative density

Density at 20 °C:

 Relative density
 Bulk density:

 Vapour density
 0.85 g/cm³
 Not determined.
 850 kg/m³
 Not determined.

Other information

· Appearance:

· Form: Aerosol

· Important information on protection of health

and environment, and on safety.

• **Ignition temperature:** Product is not selfigniting.

(Contd. on page 7)



Page 7/12

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024 Version number 2.0 (replaces version 1.0) Revision: 07.06.2024

Trade name: Mr. TOPCOAT GLOSS (Aerosol)

	(Contd. of page
· Explosive properties:	Not determined.
· Solvent content:	
· Organic solvents:	95.0 %
· VOC (EC)	95.00 %
· Change in condition	
· Evaporation rate	Not applicable.
· Information with regard to physical hazard	
classes	
· Explosives	Void
Flammable gases	Void
Aerosols	Extremely flammable aerosol. Pressurised
	container: May burst if heated.
· Oxidising gases	Void
Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit	
flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

## 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

3B **-**



Page 8/12

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024 Version number 2.0 (replaces version 1.0) Revision: 07.06.2024

Trade name: Mr. TOPCOAT GLOSS (Aerosol)

(Contd. of page 7)

## 11 Toxicological information

- Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:				
ATE (Acute Toxicity Estimates)				
Oral	LD50	24,000 mg/kg (ATE)		
Dermal	LD50	8,000 mg/kg (rab)		
Inhalative	LC50/4 h	60 mg/l (ATE)		
115-10-6	dimethyl e	ther		
Inhalative	LC50/4 h	308 mg/l (rat)		
67-63-0 pi	ropan-2-ol			
Oral	LD50	5,045 mg/kg (rat)		
Dermal	LD50	12,800 mg/kg (rabbit)		
Inhalative	LC50/4 h	30 mg/l (rat)		
64-17-5 et	hanol			
Oral	LD50	7,060 mg/kg (rat)		
Inhalative	LC50/4 h	20,000 mg/l (rat)		
78-83-1 bi	utanol			
Oral	LD50	2,460 mg/kg (rat)		
Dermal	LD50	3,400 mg/kg (rabbit)		
111-76-2 2	2-butoxye	thanol		
Oral	LD50	1,200 mg/kg (ATE)		
		1,480 mg/kg (rat)		
Dermal	LD50	400 mg/kg (rab)		
Inhalative	LC50/4 h	3 mg/l (ATE)		
01-1	! /!!4.	ation Causes skip irritation		

- Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye damage.
- · STOT-single exposure May cause drowsiness or dizziness.
- Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

## 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.

(Contd. on page 9)

Page 9/12

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024 Version number 2.0 (replaces version 1.0) Revision: 07.06.2024

Trade name: Mr. TOPCOAT GLOSS (Aerosol)

(Contd. of page 8)

- · Persistence and degradability No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- **Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

- Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

UN number or ID number		
ADR, IMDG, IATA	UN1950	
UN proper shipping name		
ADR	1950 AEROSOLS	
IMDG	AEROSOLS	
IATA	Aerosols, flammable	
Transport hazard class(es)		
ADR		
Class	2 5F Gases.	

(Contd. on page 10)



Page 10/12

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024 Version number 2.0 (replaces version 1.0) Revision: 07.06.2024

Trade name: Mr. TOPCOAT GLOSS (Aerosol)

Lahal	(Contd. of page
Label	2.1
IMDG, IATA	
Class	2.1 Gases.
Label	2.1
Packing group ADR, IMDG, IATA	not regulated
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Gases.
Hazard identification number (Kemler	,
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of litre: Category A. For AEROSOLS with a capacity
Segregation Code	above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
Maritime transport in bulk according t instruments	o IMO  Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	

— GE

Page 11/12

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024 Version number 2.0 (replaces version 1.0) Revision: 07.06.2024

Trade name: Mr. TOPCOAT GLOSS (Aerosol)

(Contd. of page 10)

· IMDG

· Limited quantities (LQ)

Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

· UN "Model Regulation": UN 1950 AEROSOLS, 2.1

### 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

(Contd. on page 12)

Page 12/12

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Version number 2.0 (replaces version 1.0) Revision: 07.06.2024 Printing date 07.06.2024

Trade name: Mr. TOPCOAT GLOSS (Aerosol)

(Contd. of page 11)

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

· Department issuing SDS: Hobby Department

· Contact: -

#### Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the

International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols – Category 1 Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity – Category 4 Acute Tox. 3: Acute toxicity – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

\* Data compared to the previous version altered.